

I CLAIM:

1 1. A garment supporting device comprising:

2 a hanger member having a central neck portion and
3 opposing shoulder portions extending from opposite edges of said
4 neck portion to a predetermined point for supporting a first
5 garment piece with shoulder portions;

6 a suspension hook at said neck portion for engaging a
7 support for said hanger member;

8 a first bar affixed between said predetermined points
9 on each of said opposing shoulder portions of said hanger member
10 disposed in a first generally horizontal plane; and

11 a second bar coupled with said first bar and rotatable
12 outwardly therefrom at fixed angular stops with respect thereto
13 for supporting a second garment piece with leg portions;

14 with one of said angular stops placing said second bar
15 in substantially the same generally horizontal plane as said
16 first plane and with another of said angular stops placing said
17 second bar in a generally horizontal plane above or below said
18 first plane.

1 2. The garment supporting device of Claim 1 wherein said
2 second bar is coupled with said first bar by a rotatable hinge.

1 3. The garment supporting device of Claim 1 wherein said

2 second bar is coupled with said first bar by a rotatable hinge
3 having fixed cut-out stops at predetermined angular intervals
4 thereon.

1 4. The garment supporting device of Claim 1 wherein said
2 second bar is coupled with said first bar by a rotatable hinge
3 having fixed cut-out stops at predetermined angular intervals
4 thereon of 30° spacing.

1 5. The garment supporting device of Claim 3 wherein said
2 rotatable hinge is spring actuated to lock said second bar
3 within each of said cut-out stops.

1 6. The garment supporting device of Claim 1 wherein said
2 hanger member and said first and second bars are each of a wood
3 composition.

1 7. The garment supporting device of Claim 1, also including
2 a resilient garment contact member fixedly secured at one end of
3 said second bar and running along said second bar toward an
4 opposite end thereof to be temporarily secured thereat in
5 holding said second garment piece in place.

1 8. The garment supporting device of Claim 2 wherein said
2 first and second bars and said rotatable hinge are incorporated
3 with said hanger member as an integral manufacture.

1 9. The garment supporting device of Claim 2 wherein said
2 first bar is incorporated with said hanger member as a first
3 integral manufacture, and wherein said second bar is
4 incorporated with said hinge as a second, separate integral
5 manufacture in joining therewith to form said garment supporting
6 device.